



ASSOCIATION CONNECTING
ELECTRONICS INDUSTRIES®

IPC-2251

Design Guide for the Packaging of High Speed Electronic Circuits

Developed by the IPC-2251 Task Group (D-21a) of the High Speed/
High Frequency Committee (D-20) of IPC

Supersedes:

IPC-D-317A - January 1995

IPC-D-317 - April 1990

Users of this publication are encouraged to participate in the
development of future revisions.

Contact:

IPC
2215 Sanders Road
Northbrook, Illinois
60062-6135
Tel 847 509.9700
Fax 847 509.9798

Table of Contents

1 GENERAL	1	4.4 Component Placement	17
1.1 Purpose	1	4.4.1 Crosstalk Management.....	17
1.2 Scope	1	4.4.2 Impedance Control.....	17
1.3 Symbology, Terms and Definitions	1	4.4.3 Power Distribution	18
1.3.1 Symbology	1	4.4.4 Thermal Management.....	18
1.3.2 Terms and Definitions.....	2	4.4.5 System Cost.....	18
1.4 Units	6	5 ELECTRICAL CONSIDERATIONS	18
2 APPLICABLE DOCUMENTS	6	5.1 Power Distribution	18
3 OVERVIEW	6	5.1.1 System DC Model.....	18
3.1 Decision Making Process	6	5.1.2 Power Plane Impedance.....	19
3.2 Design Options.....	7	5.1.3 Integrated Circuit Decoupling	20
3.2.1 System Electrical/Mechanical Constraints	7	5.1.4 Decoupling Capacitance and Plane Capacitance	22
3.2.2 Signal Integrity Design Constraints	8	5.1.5 Device Power Dissipation.....	25
3.2.3 System Electrical/Mechanical Requirements	9	5.2 Permittivity	25
3.3 Mechanical Requirements.....	9	5.2.1 Relative Permittivity	25
3.3.1 Circuit Board.....	10	5.2.2 Effective Relative Permittivity	25
3.3.2 Hybrid.....	10	5.2.3 Frequency Dependence	26
3.3.3 Component Packaging	10	5.3 Lumped Capacitance Versus Transmission Line Environment	28
3.3.4 Thermal Management	10	5.4 Propagation Delay Time	30
3.3.5 Component Mounting	10	5.4.1 Capacitive Line	30
3.4 Electrical Considerations	10	5.4.2 Transmission Line.....	30
3.4.1 Power Distribution	10	5.5 Impedance Models	31
3.4.2 Permittivity.....	10	5.5.1 Microstrip	31
3.4.3 Capacitive Versus Transmission Line Environment	11	5.5.2 Embedded Microstrip.....	32
3.4.4 Propagation Time	11	5.5.3 Centered Stripline	33
3.4.5 Characteristic Impedance	11	5.5.4 Dual-Stripline	33
3.4.6 Signal Loading Effects.....	11	5.5.5 Differential Pair Conductors.....	34
3.4.7 Crosstalk.....	12	5.6 Loading Effects	36
3.4.8 Signal Attenuation.....	12	5.6.1 Termination Resistors	36
4 MECHANICAL CONSIDERATIONS	12	5.6.2 Reflections.....	36
4.1 Printed Board	12	5.6.3 Minimum Separation.....	36
4.1.1 Substrate Materials.....	12	5.6.4 Distributed Loading	38
4.2 Component Packaging	14	5.6.5 Lumped Loading.....	39
4.2.1 Device.....	14	5.6.6 Radial Loading.....	40
4.2.2 Connectors.....	14	5.6.7 Logic Signal Line Loading Models	41
4.2.3 Cables	15	5.6.8 Timing Calculation.....	42
4.3 Thermal Considerations	15	5.7 Crosstalk.....	44
4.3.1 System Level Impacts.....	15	5.7.1 Model.....	44
4.3.2 Board Level Impacts.....	15	5.7.2 Microstrip Transmission Line.....	46
4.3.3 Device Level Impacts	16	5.7.3 Embedded Microstrip Transmission Line	46
		5.7.4 Backward Crosstalk Amplitudes.....	46

5.7.5	Stripline	46	Figure 5-5	Capacitive and Transmission Line Current Pulses – A) is for a very short line and B) is for a long line	21
5.7.6	TTL/MOS Models.....	47	Figure 5-6	Fourier Transform	22
5.8	Signal Attenuation.....	47	Figure 5-7	Capacitor Equivalent Circuit	23
5.8.1	Resistive Losses (Skin Effect).....	47	Figure 5-8	(a) through (m) Typical Impedance Structures.....	27
5.8.2	Dielectric Losses	48	Figure 5-9	ϵ_r and $\tan \delta$ versus frequency for FR-4.....	28
5.8.3	Rise Time Degradation	48	Figure 5-10	Capacitive Loading	30
5.9	Computer Simulation Program.....	49	Figure 5-11	Wire Over Reference Plane	31
5.9.1	Computer Simulation Models.....	49	Figure 5-12	Flat Conductor Surface Microstrip.....	32
5.10	Connectors	49	Figure 5-13	Flat Conductor Embedded Microstrip.....	32
5.10.1	Sensitivity.....	49	Figure 5-14	Flat Conductor Centered Stripline	33
5.10.2	Distributed Line Compensations	49	Figure 5-15	Wire Conductor Centered Stripline.....	33
5.10.3	Connector Types.....	49	Figure 5-16	Flat Conductor Dual Stripline (Asymmetrical Signals)	34
5.11	EMI Layout Considerations	49	Figure 5-17	Wire Conductor Differential Centered Stripline	34
5.11.1	Reasons for Considering EMI Layout	49	Figure 5-18	Flat Conductor Shielded Broadside Coupled Differential Stripline	35
5.11.2	Digital Edge Rates	50	Figure 5-19	Flat Conductor Nonshielded Broadside Coupled Differential Stripline	35
5.11.3	Suggested EMI Layout Practices	50	Figure 5-20	Flat Conductor Shielded Edge Coupled Differential Stripline.....	35
6	PERFORMANCE TESTING	52	Figure 5-21	Flat Conductor Shielded Edge Coupled Differential Dual Stripline	35
6.1	Impedance Testing	52	Figure 5-22	Flat Conductor Edge Coupled Differential Surface Microstrip.....	36
6.1.1	Principle of Impedance Testing Using a TDR.....	52	Figure 5-23	Flat Conductor Edge Coupled Differential Embedded Microstrip.....	36
6.1.2	Impedance Measuring Test Equipment	52	Figure 5-24	Net Illustrating Point Discontinuity Waveforms	37
6.2	Impedance Test Structures and Test Coupons ...	52	Figure 5-25	Addition of Two Pulses Traveling Opposite Directions	37
6.2.1	Test Structure Design.....	52	Figure 5-26	Distributed Line.....	38
6.2.2	Test Probes and Connections.....	53	Figure 5-27	Lumped Loading.....	39
6.2.3	Locating Impedance Test Structures	53	Figure 5-28	Short Distributively Loaded Cluster	39
6.2.4	A Simple Impedance Test Method.....	53	Figure 5-29	a) Lumped Loaded Transmission Line b) Equivalent Model.....	39
6.3	Stripline Impedance Test Coupon	53	Figure 5-30	Waveforms for a Lumped Capacitive Load	39
Appendix A	55	Figure 5-31	Lumped Transmission Line.....	40
Appendix B	76	Figure 5-32	Radial Loading.....	40
Appendix C	80	Figure 5-33	Example Configuration	40
Appendix D	82	Figure 5-34	Example of Radial Line	41

Figures

Figure 3-1	High-Speed Packaging Design Concept	7	Figure 5-35	Net Configuration.....	41
Figure 4-1	Schematic of Information, Electrical Power and Enthalpy (Heat) Flows	16	Figure 5-36	Bus Configuration	41
Figure 4-2	Heat Flux vs. Component Area	16	Figure 5-37	Wired-AND Configuration	42
Figure 4-3	Component Placement Guideline.....	17	Figure 5-38	Multiple Reflections In A Transmission Line Between Two TTL Inverters.....	43
Figure 5-1	DC Distribution Model.....	18	Figure 5-39	Equivalent Circuit Example (top) with Corresponding Lattice Diagram (bottom)	44
Figure 5-2	DC Power Distribution System (Without Remote Sensing).....	20	Figure 5-40	Predicted Driver (A) and Load (B) Waveforms for Figure 5-39.....	44
Figure 5-3	Decoupling Impedance Modeling - Power Supply	20	Figure 5-41	Induced Crosstalk Voltages	45
Figure 5-4	Device Decoupling Model.....	21			

Figure 5-42	Crosstalk Voltages for a Line Terminated at Both Ends	45
Figure 5-43	Drivers and Receivers at a Common End	47
Figure 5-44	Drivers and Receivers at Opposite Ends	47
Figure 5-45	AC Noise Immunity for Selected TTL Families	48
Figure 6-1	TDR Impedance Test Coupon	54
Figure 6-2	Test Setup for Measuring Conductor Impedance (Suitable for Receiving Inspection)	54

Tables

Table 4-1	Wire Resistivity	13
Table 5-1	Copper Wire Characteristics	19
Table 5-2	Copper Busbar Resistances/ft	19
Table 5-3	Impedance for 0.1 μ F and 0.001 μ F DIP and 1206 Capacitors	23
Table 5-4	Typical Data for Some Logic Families	29
Table 5-5	Logic Model Classifications	36
Table 5-6	Connector Equivalent Bandwidth	50

Design Guide for the Packaging of High Speed Electronic Circuits

1 GENERAL

1.1 Purpose The object of this document is to provide guidelines for the design of high-speed circuitry. The subjects presented here represent the major factors that may influence a high-speed design. This guide is intended to be used by circuit designers, packaging engineers, circuit board fabricators, and procurement personnel so that all may have a common understanding of each area.

1.2 Scope The goal in electronic packaging is to transfer a signal from one device to one or more other devices through a conductor. Considerations include electrical noise, electromagnetic interference, signal propagation time, thermo-mechanical environmental protection, and heat dissipation. High-speed designs are defined as designs in which the interconnecting properties affect circuit function and require consideration. Every electrical concept has relevant physical implementation data and limitations provided to match the electrical and mechanical relationships. This guideline presents first order approximations for each of the subject areas covered. If more detail is required, the papers presented in the bibliography may provide more detailed supplemental data. Since most high speed design requires signal intergity and EMI techniques, often field solvers, signal integrity simulation tools, EMI/EMC simulation programs may be required for resolving design challenges. Many PWB layout design tools include these tools as options to their programs. These simulators are driven by SPICE, IBIS, or other models. References to manufacturers of these tools may be found on the IPC Web site (www.ipc.org).

1.3 Symbology, Terms and Definitions

1.3.1 Symbology

Symbol	Description
--------	-------------

ABT	Advanced Bipolar-CMOS Technology
AC	Advanced CMOS
AC	Alternating Current (Time varying current)
ACQ	Advanced CMOS Quiet
ACT	Advanced CMOS TTL Compatible
ACTQ	Advanced CMOS TTL Compatible Quiet
AGP	Advanced Graphics Port Logic
AHC	Advanced High-Speed CMOS
AHCT	Advanced High-Speed CMOS TTL Compatible

ALS	Advanced Low Power Schottky Technology
AS	Advanced Schottky Technology
BCT	Bipolar-CMOS Technology
CMOS	Complimentary Metal Oxide Semiconductor
COB	Chip-On-Board
CTE	Coefficient of Thermal Expansion
CTE _{XY}	X and Y-Axis Coefficient of Thermal Expansion
CTE _Z	Z-Axis Coefficient of thermal expansion
CTT	Center Tap Terminated Logic
DC	Direct Current
DIP	Dual In-line Package
DWB	Discrete Wiring Board
dV/dT	Delta Voltage/Delta Time (Edge Slew Rate)
ECL	Emitter Coupled Logic
EMI	Electromagnetic Interference
ESD	Electro-Static Discharge
F	Fast Bipolar Logic Technology
FR-4	Flame Retardant Level 4, Epoxy Glass Dielectric Material
GaAs	Gallium Arsenide Technology
GTL	Gunning Transceiver Logic
GTL+	Gunning Transceiver Logic Plus
HC	High-Speed CMOS Technology
HCT	High-Speed CMOS TTL Compatible
HL	High-to-Low Signal Edge Transition
HSTL	High-Speed Transceiver Logic
IBIS	I/O Buffer Information Specification
IBuf	Input Buffer
IC	Integrated Circuit
K _B	Backward Crosstalk
K _F	Forward Crosstalk
L _G	Ground Plane Inductance
L _H	Low-High Signal Edge Transition
L _P	Power Plane Inductance
LVDS	Low Voltage Differential Signalling
LVEL	Low Voltage ECL
LVPECL	Low Voltage PECL
LVC MOS	Low Voltage CMOS Technology
LVT	Low Voltage Technology